

POWER TOOL OPTIONS

FROMM | STRAPPING SOLUTIONS



DATA SHEET P328S

Battery powered **TOUCH SCREEN** operated manual plastic strapping tool for PP and PET strap

Battery powered, Digitalized, plastic strapping tool



) 9.0 Ah battery is one of the **Smart efficiency and cost saving options the FROMM P328S offers its operators. Only available in the EU countries.

Characteristics

Strapping qualities	Polyester (PET) and Polypropylene (PP) plain and embossed
Strapping dimensions	width 12.0 – 16.0 mm / ½ - ⅝" thickness 0.40 – 1.05 mm / .016 – .041"
Weight incl. 4.0 Ah battery	4.3 kg / 9.6 lbs
Tool size with 4.0 Ah battery	L351 x W134 x H143 mm / 13.8 x 5.3 x 5.6"
Type of seal	Friction welding
Average seal strength	approx. 75% (dependent on the strap quality)
Tension force	250 – 2.600 N / 56 – 585 lbs (adjustable)
Tension speed	49 – 174 mm/s / 1.9 – 6.8 inch/s
Power supply	Battery Li-Ion 18 VDC / 4.0 Ah or 9.0 Ah
Suspension brackets	optional

Features that matter

- Strap database management, updating and service readout with **W**ireless Technology (Option) will tell you when service is advised;
- The Smart, all-in-one and easy to operate slanted colour touch screen, is always located in-sight of the operator, preventing water and dust from entering the device here;
- One-hand operation 3-in-1 tool, easy selecting manual, semi-automatic or automatic operation;
- Setting and locking the right tension force, speed and sealing time at the touch of a finger;
- Tested to meet or exceed the high FROMM quality standards and customer expectations;
- Pre-stored strap types with the 10 free configurable strap modes help to set the tool right;
- Durable design, Easy-to-Recycle, with double strap guides for "AlwaysGood" strap alignment;
- Easy inserting and removing the strap, no obstacles from hands or other barriers;
- Well balanced tool with extra finger protection for safe and good working conditions;
- Sturdy battery holder that can accommodate 4.0 Ah or 9.0 Ah batteries with charge indicator;
- Brushless motor, with motor temperature monitoring system. Optional motor cooling fan available for extreme environments;
- Easy cleaning, removing strap dust particles with pressurized air.