



LD-19SB

Low profile/narrow uniform case sealer

Heavy Duty Construction

Heavy duty construction, designed specifically for low profile/narrow – uniform box runs

Simple & Reliable Operation

Push button start controls, e-stop and single mast design ensure safety for the operator

Production Versatility

Capable of processing a case as low as 63.5 mm (2.5 in) and as narrow as 89 mm (3.25 in)

Quick/Easy Changeover

Simple slide and lock adjustment for case height and turn handle to adjust for case width

LD-19SB

Low profile/narrow uniform case sealer

The LD-19SB is an industrial grade, high performance case sealer from Little David®.

This case sealer is designed to seal low profile and narrow case sizes and is unrivaled in its efficiency, easy-of-maintenance, and durability.

The LD-19SB needs only 2 adjustments for the height and width of the case. The adjustments are fixed in place to process a series of uniform cases. Cases are top and bottom sealed with either 51 mm (2 in) or 76 mm (3 in) tape

Features and benefits

■ Performance

- Processes low profile and narrow cases
- Continuous belt drive speed of 22 meters (72 feet) per minute

■ Versatility

- Expansive case size range
- Simple slide and lock adjustment for height and turn handle to adjust for width.
- Interchangeable cartridges (top and bottom)

■ Durability

- Heavy-duty steel construction

■ Safety

- Push button start controls
- E-stop button
- Single mast design ensures safety for the operator

Optional equipment

- Spare parts kit
- Casters
- Pack table
- Spare tape cartridge
- Up-charge for one inch tab tape cartridges
- Spare CaseLocker 60™ one inch tab tape cartridge
- Mirror image
- Increased conveyor height
- 3 phase motor
- NEMA 4 or 12 electrical package



LD-19SB Technical Specifications

Power	115 volts, 60 cycle, single phase
Air	None
Operating Speed	Continuous belt drive 22 meters/minute (72 feet/minute)
Case Capacity	Length: 127 mm (5 in) - infinite Width: 82.55 mm (3.25 in) - 508 mm (20 in) Height: 63.5 mm (2.5 in) - 609 mm (24 in)
Machine Dimensions	Length: 127 cm (50 in) Width: 99.1 cm (39 in) Height: 170 cm (57.25 in)
Conveyor Height	61.6 cm (24.25 in) - 74.3 cm (29.25 in) Standard - Consult factory for other heights
Warranty	1 Year
Closure Material	Pressure Sensitive Tape



CaseLocker™ 60 series tape cartridges

- Patented locking knife guard system allows the blade to be exposed only when the rollers are depressed
- Telescoping tape core allows for varying tape core sizes
- Patented tool-less removal of blades and wipe rollers
- Processes weak corrugated
- No lubrication points
- Utilizes link bar and knife arm bearings for added strength



SIGNODE

Loveshaw/Little David
1-800-572-3434
marketing@loveshaw.com